	<b>BOSSIL TECHNOLOGY SDN. BHD.</b>	<b>Issued Date:</b> 08/01/15 <b>Revision No.:</b> 0 <b>Revised Date:</b> -
	Technical Data Sheet	<b>Page:</b> 1 Of 2
	<b>BS-2640 Rainbow Fill</b>	

**Product Specification:**

Base	Acrylic Latex
Appearance	Non-Sagging Paste
Colour	White, Grey, Brown, Teak, Light Brown, Black, Cherry, Beige, Merbau and Terracotta.
Odour	Mild Acrylic Odour
Specific Gravity (g/mL)	Approximately 1.58
Solids Content	80 - 82%
Extension Recovery (ASTM C736)	90%
Slump Test (ASTM D2202)	No Slump
Stain Index (ASTM D2203)	No Stain
Tack Free Time (ASTM D2377)	No adhering material to plastic strip.
Shore A Hardness (ASTM D2240)	30 (Approx.)
Paint Ability	Paintable
Freezing Point	0° C
Application Temperature	5°C to 50°C
Service Temperature	-10°C to 75°C

**Features:**

- Water Based / Easy Clean Up
- Dries True to Wet Color
- Flexible / Paintable Gap Sealant








**Product Description:**

A one component, paintable and flexible, premium quality acrylic sealant formulated for sealing of gaps and joints where slight movement or vibration causes conventional, non-elastic fillers and putties to crack and fall out. It had good adhesion to most porous surfaces without primer and is economy yet environmental friendly that can be cleaned up with water. It uses the clear cartridge to enable the user to choose the color that matches their building materials.

**Applications:**

With the vast color selection, one can match the color of the bonding / sealing to the color of the Wood / Timber, concrete, marble, glass, plastic etc. It is also use for joint around the door and windows.

Timber Skirting / Flooring	Kitchen Cabinet (Gap Sealing)	Window Frame (Connecting Joints)	Door Frame
			

	<b>BOSSIL TECHNOLOGY SDN. BHD.</b>	<b>Issued Date: 08/01/15</b>
	Technical Data Sheet	<b>Revision No.: 0</b>
	<b>BS-2640 Rainbow Fill</b>	<b>Revised Date: -</b>
		<b>Page: 2 Of 2</b>

#### Directions:

- Surfaces must be clean, dry and free of dirt, grease, oil or water.
- Cut nozzle at 45° angle to desired bread-width and apply to substrate with cartridge gun.
- Apply the sealant in a continuous bead using enough pressure to properly fill the joint.
- Tooling time is 20 minutes, tack free time is 30 minutes. Allow to skin for 1 hour before applying water-based paint and 24 hours for oil-based paints.
- Uncured sealant can be cleaned up with damp cloth.

#### Limitations:

It should not be applied outdoors if it is likely to be rained upon within 2 hours of application.

Not For: Use in areas of constant water immersion.

Not For: Joint movement more than 10%.

#### Caution:

- Avoid contact with eyes, skin and mouth.
- Use in well-ventilated area. In case of contact with eyes, flush with water immediately for 15 minutes. If irritation persists, seek medical attention.
- Keep out of reach of children.

#### Storage:

- Store in a dry and cool place with temperature below +30°C.
- Use within 24 months from date of production.

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of various of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.

- END -